

MIAMI-DADE COUNTY, FLORIDA METRO-DADE FLAGLER BUILDING 140 WEST FLAGLER STREET, SUITE 1603 MIAMI, FLORIDA 33130-1563 (305) 375-2901 FAX (305) 375-2908

# **NOTICE OF ACCEPTANCE (NOA)**

KML Windows, Inc. 23 Buchanan Court London, Ontario, Canada N5Z 4P9

# Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the High Velocity Hurricane Zone of the Florida Building Code.

#### **DESCRIPTION:** Aluminum Clad Wood Slash Glazed Wood Fixed Window-Impact.

**APPROVAL DOCUMENT:** Drawing No.**1226A**, titled "Aluminum Clad Wood Slash Glazed Wood Fixed - Impact Windows", sheets 1 through 8 of 8, prepared by W.W. Schaefer Engineering & Consulting, P.A., dated 5/13/03, signed and sealed by Warren Schaefer, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Division.

#### MISSILE IMPACT RATING: Large and Small Missile Impact

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA # 00-1030.06 and, consists of this page 1 as well as approval document mentioned above. The submitted documentation was reviewed by **Theodore Berman**, **P.E.** 

NOA No 03-0625.04 Expiration Date: September 20, 2006 Approval Date: October 16, 2003

Page 1

### KML Windows, Inc.

## NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

#### A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- 2. Drawing No.**1226A**, titled "Aluminum Clad Wood Slash Glazed Wood Fixed Impact Windows", sheets 1 through 8 of 8, prepared by W.W. Schaefer Engineering & Consulting, P.A., dated 5/13/03, signed and sealed by Warren Schaefer, P.E.

#### B. TESTS

- 1. Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
  - 2) Large Missile Impact Test per FBC, TAS 201-94
  - 3) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of a wood fixed window, prepared by Architectural Testing, Inc., Test Report No. ATI 02-35024.02, dated 5/28/03, signed and sealed by Steven Urich, P.E.

# Submitted under NOA# 00-1030.06

- 1. Test reports on 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94
  - 4) Large Missile Impact Test per FBC, TAS 201-94
  - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
  - 6) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94

along with marked-up drawings and installation diagram of a wood fixed window, prepared by Intertek Testing Services, Test Report No. ITS-J99022770-231-03, dated October 9, 2000, signed and sealed by Douglas Keith Tucker, P.E.

- 2. Test reports on 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94

along with marked-up drawings and installation diagram of a wood fixed window, prepared by Intertek Testing Services, Test Report No. ITS-J99022770-231-04, dated October 9, 2000, signed and sealed by Douglas Keith Tucker, P.E.

- 3. Test reports on 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94
  - 4) Large Missile Impact Test per FBC, TAS 201-94
  - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
  - 6) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94

along with installation diagram of aluminum clad wood operable casement windows of different shapes, prepared by Intertek Testing Services, Inc., Report No. ITS-J990225770-231-05, dated October 10, 2000, signed and sealed by

Douglas Keith Tucker, P.E.

Theodore Berman, P.E.

**Deputy Director, Product Control Division** 

NOA No 03-0625.04

Expiration Date: September 20, 2006 Approval Date: October 16, 2003

## KML Windows, Inc.

## NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

- 4. Test reports on 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94

along with installation diagram of aluminum clad wood operable casement windows of different shapes, prepared by Intertek Testing Services Inc., Test Report No. **J99022770-231-06**, dated October 11, 2000, signed and sealed by Douglas Keith Tucker, P.E

Addendum letter dated March 20, 2001, signed and sealed by Douglas Keith Tucker, P.E

(#3 & #4 are for reference only, to qualify the side-by-side configuration)

#### C. CALCULATIONS

1. Anchor Calculations, ASTM-E1300-98 and structural analysis, dated 5/22/03, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren Schaefer, P.E.

# Submitted under NOA# 00-1030.06

1. Anchor Calculations and structural analysis prepared by W. W. Schaefer Engineering & Consulting, P.A., dated 08/23/00, signed and sealed by Warren W. Schaefer, P.E.

#### D. MATERIAL CERTIFICATIONS

#### Submitted under NOA# 00-1030.06

1. Notice of Acceptance No. **00-0524.06** issued to Nebula Glass International Inc. for "Glasslam Safety-Plus Laminated Glass" dated 9/21/00, expiring on 9/9/03.

#### E. QUALITY ASSURANCE

1. Miami Dade County Building Code Compliance.

## F. STATEMENTS

1. Laboratory compliance letter issued by Architectural Testing, Inc., Test Report No. **ATI 02-35024.02**, dated 5/28/03, signed and sealed by Steven Urich, P.E.

#### G. OTHER


1. Notice of Acceptance No. **00-1030.06**, issued to KML Window, Inc., Aluminum Clad Wood Slash Glazed Wood Fixed Window, approved on 9/20/01 and expiring on 9/20/06.

Theodore Berman, P.E.

Deputy Director, Product Control Division NOA No 03-0625.04

**Expiration Date: September 20, 2006** 

Approval Date: October 16, 2003




NOTE: FOR COMBINATION OF UNITS. SEE MULLION DRAWING NO. 1003E UNDER SEPERATE APPROVAL

# SIZE NOTE:

WINDOW SIZE & LOAD SHALL BE LIMITED BY THOSE SIZES & LOADS SPECIFIED IN THE LOAD TABLES ON SHEET 7.

HEIGHT	MAX. ALLOWABLE WIDTH
126"	57"
132"	54"
138"	52"
144"	50"

ALLOWABLE DESIGN LOADS SEE "LOAD TABLE" ON SHEET T



SCALE: 1/2"=1'-0'

(60" X 120" SIZE SHOWN. FOR OTHER APPLICABLE

MAXIMUM SIZES, SEE LOAD TABLE ON SHEET 7)

# GENERAL NOTES

- THESE WINDOW SYSTEMS HAVE BEEN TESTED, ANALYZED AND APPROVED FOR DESIGN PRESSURES NOT TO EXCEED THOSE SHOWN IN THE LOAD TABLES ON SHEET 1, 2 & 7.
- 2. BUCKING, OPENINGS & BUCKING FASTENERS MUST BE DESIGNED & INSTALLED TO WITHSTAND WIND LOADS AS DETERMINED FOR EA. APPLICATION
- 3. ALL HARDWARE & FASTENERS SHALL BE IN ACCORDANCE WITH THESE DRAWINGS & MAY NOT VARY UNLESS SPECIFICALLY MENTIONED ON THE DRAWINGS.
- 4. THE DETAILS & SPECIFICATIONS SHOWN HEREIN REPRESENT THE PRODUCTS PROPOSED FOR WATER, AIR, IMPACT, CYCLIC & UNIFORM STATIC AIR PRESSURE TESTING IN CONFORMANCE WITH FLORIDA BUILDING CODE PROTOCOLS TAS 201, 202 & 203 FOR IMPACT WINDOWS.
- 5. ALL JAMB TO BUCKING SHEAR FASTENERS MUST PENETRATE BUCK A MINIMUM OF 1 3/8". IF PENETRATION IS LESS THAN 1 3/8" THEN SCREW LENGTH SHALL INCREASE AS REQUIRED.
- 6. THESE WINDOW SYSTEMS HAVE BEEN DESIGNED IN ACCORDANCE WITH THE FLORIDA BUILDING CODE (FBC).
- 7. THIS PRODUCT HAS BEEN TESTED IN ACCORDANCE WITH FLORIDA BUILDING CODE PROTOCOLS TAS-201, 202 & 203 FOR LARGE MISSILE IMPACT, STRUCTURAL & CYCLIC TESTING.
- 8. THE LARGER WINDOW DIMENSION MAY BE EITHER HORIZONTAL OR VERTICAL

# JAMB FASTENER MIN. EMBEDMENT INTO OPENING OR BUCK

NO. 10 SMS SCREWS INTO BUCK = 1.3/8" 1/4" TAPCON INTO CONCRETE/BLOCK = 1 1/4"

# JAMB FASTENER MINIMUM EDGE DISTANCE AT OPENING OR BUCK

WOOD BUCK = 1" CONCRETE/BLOCK == 2"

> PRODUCT REVISED as complying with the Florids Acceptance No 03-0025 Mianti Dade Product Control

CERTIFICATION	EMPL 8 1 NN	WARREN W. SCHAFFER, P.E.
Dr	1226A	nev.
	SHEET NO.	

or 8

CHECKED BY: W.W.S. 05/13/03

KML WINDOWS, INC.

3 BUCHANAN COURT
ONTARIO, CANADA N5Z4P9
(519) 681-7012

23 LONDON, O

WINDOWS

IMPACT

FIXED

GLAZED

SASH


WOOD


CLAD


ΧÃ


NITS SCHAEFER ENGINEERING CONSULTING, P.A.

W. SCHAE
W. SCHAE
& CONSI
8895 N. MILITA
PALM BEACH
ONE: 561-775-4









# TYPICAL GLASS & GLAZING DETAIL

SCALE: 3/4 FULL SIZE

GLASS OPTION 1: NEBULA SAFETY-PLUS (3/16" HS/0.06" RESIN/ 0.01" PET/0.06"


RESIN/3/16" HS)

GLASS OPTION 2: NEBULA SAFETY-PLUS (1/4"

HS/0.06" RESIN/ 0.01" PET/0.06"

SCALE: N.T.S.

RESIN/1/4" HS)



# TYPICAL GLASS & GLAZING DETAIL

SCALE: 3/4 FULL SIZE

GLASS OPTION 3: 9/16" THICK LAMINATED GLASS WITH DUPONT

SGP (1/4" HS/0.09" SGP/1/4" HS)

GLASS OPTION 4: 9/16" THICK LAMINATED GLASS WITH SAFLEX PVB (1/4" AN/0.09" PVB/1/4" AN)

GLASS OPTION 5: 3/8" THICK LAMINATED GLASS WITH SAFLEX PVB (5/32" AN/0.09" PVB/5/32" AN)

SCALE: N.T.S.

12" O.C. TAPCON LENGTH AS REQUIRED FOR MIN 1 1/4" CONC. OR BLOCK EMBED

2" MIN.

1X4 P.T. AS REQ'D

9B

16


78

222


1/4" TAPCON 4" FROM CORNERS AND MAX .-

# OPTIONAL JAMB DETAIL FOR DIRECT MOUNT TO CONCRETE OR BLOCK

(TYP. ALL UNITS) SCALE: 1/2 FULL SIZE



JAMB CORNER DETAILS



# SASH STILE TO RAIL CORNER DETAIL

SCALE: N.T.S.

NOTE: CLAD CORNER IS MITERED & FASTENED WITH

1 NO. 6 X 1" SMS INTO SPLINE & GASKETED

WITH 31 (SIMILAR TO JAMB CLAD CORNERS EXCEPT

WITH ONE SCREW)



CERTIFICATION

CERTIFICATION

ON DAIMAND

SOLABFER, P.E.

POST OF THE PROPERTY OF THE PROPERTY

CHECKED BY

05/13/03


RAWN BY:

WINDOWS

FIXED

GLAZED

CLAD



DESIGN LOAD CAPACITY (PSF)							DE	SIGN	LOA	D CA	PACI	ry (F	SF)						
I	WINDOW GLASS GLASS GLASS SIZE OPTION OPTION OPTION			WIN		GLASS OPTION		GLASS		GLASS OPTION		1	ASS TION						
(OSM) 1		1	2 & 3   4			5 OPTION			SIZE (OSM)		1		OPTION 2 & 3		4		5		
MAX.	MAX.	-	i I	-			i I	· ·		MAX.	MAX.		·	-			i T	<u> </u>	
SHORT	LONG									SHORT	1								
SIDE	SIDE	POS	NEG	POS	NEG	POS	NEG	POS	NEG	SIDE	SIDE	1	NEG	POS	NEG	POS	NEG	POS	NEG
24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
30"	36"	70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	30"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
36"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	36"		70.0	80.0	70.0	80.0	70.0	80.0	58.7	58.7
24"	-	70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	42"	70"	70.0	80.0	70.0	80.0	70.0	80.0	-	
30" 36"	42"	70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	48" 54"	78"	70.0	80.0	70.0	80.0	70.0	80.0	-	
42"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	60"		70.0	80.0	70.0	80.0	70.0	73.4	<del>-</del> -	_
24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	66"		63.6	72.7	63.6	72.7	<del>  _</del>	<del>  _</del>	<del>                                     </del>	_
30"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	72"		58.3	66.7	58.3	66.7	_	_	_	-
36"	48"	70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
42"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	73.5	30"	-	70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
48"		70.0	80.0	70.0	80.0	70.0	80.0	64.2	64.2	36"		70.0	80.0	70.0	80.0	70.0	80.0	56.3	56.3
24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0	42"		70.0	80.0	70.0	80.0	70.0	80.0		
30"		70.0	80.0		80.0	70.0	80.0	70.0	80.0	48"	84"	70.0	80.0	70.0	80.0	70.0	80.0		-
36"	54"	70.0	80.0		80.0	70.0	80.0	70.0	79.3	54"		70.0	80.0	70.0	80.0	68.2	68.2		
42"			80.0		80.0			64.4	64.4	60" 66"		70.0	74.3	70.0	80.0				
48" 54"			80.0		80.0		80.0	56.8 -	56.8	72"		63.6 58.3	72.7 66.7	63.6 58.3	72.7 66.7	_	_		
24"			80.0		80.0		80.0	70.0	80.0	24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
30"			80.0		80.0	_	80.0	70.0	80.0	30"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
36"			80.0					70.0	71.9	36"		70.0	80.0		80.0	70.0	80.0	_	_
42"	60"	70.0	80.0	70.0	80.0	70.0	80.0	57.5	57.5	42"		70.0	80.0	70.0	80.0	70.0	80.0	_	_
48"	60	70.0	80.0					50.3	50.3	48"	90"	70.0	80.0	70.0	80.0	70.0	77.2		
54"			80.0		80.0		80.0			54"		70.0	75.4	70.0	80.0		_		
60"					80.0		80.0			60"		68.8	68.8	70.0	80.0				
66"			0.08				80.0	-	-	66"			72.7		72.7				
24" 30"			$\overline{}$						80.0	72 <b>"</b> 24"		58.3	66.7		66.7	70.0	- 00.0	70.0	-
36"					80.0	+			80.0 65.8	30"		70.0 70.0			80.0		0.08		80.0
42"									52.4	36"	ŀ	70.0					80.0	70.0	-
48"	66"						80.0	_	_	42"		70.0					80.0	_	_
54"							80.0	-	_	48"	96"						74.0	_	_
60"		70.0	80.0	70.0	80.0	70.0	76.7	_	-	54"	[	70.0	71.8	70.0	80.0	-		_	_
66"							68.2			60"		63.5			80.0				
24"	- t								80.0	66"		63.6			72.7				
30"	- 1								80.0	72"					66.7				
36"									61.5	24"	ŀ				80.0		80.0		80.0
42" 48"	F						80.0	47.4	47.4	30" 36"	}						80.0		
54"	}						79.6	_		42"	Ī						80.0		
60"	- F						69.7	_	_	48"	11172 1				80.0		-	_	
66"	-				72.7	-	_	_		54"	ř	68.1			80.0	-	-	_	-
72"					66.7	-	- 1	-		60"				$\overline{}$	80.0				
										66"		63.6	66.8	63.6	72.7				

	DESIGN LOAD CAPACITY (PSF)									
	WIND	OOW	GLASS		GL	GLASS		ASS	GLA	ASS
	SIZ	ZΕ	OPTION			OPTION		OPTION		ION
	(08	M)		1	2 8	2 & 3		4		5
	MAX.	MAX.								
	SHORT	LONG			İ		ŀ			
	SIDE	SIDE	POS	NEG	POS	NEG	POS	NEG	POS	NEG
	24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
	30"		70.0	80.0	70.0	80.0	70.0	80.0	_	_
	36"		70.0	80.0	70.0	80.0	70.0	80.0		
	42"	108"	70.0	80.0	70.0	80.0	70.0	80.0		
	48"	100	70.0	78.6	70.0	80.0				
	54"		64.4	64.4	70.0	80.0				
╛	60"		56.7	56.7	70.0	80.0				
╛	66"		62.0	62.0	63.6	72.7		_		
╛	24"		70.0	80.0	70.0	80.0	70.0	80.0	70.0	80.0
╛	30"		70.0	80.0	70.0	80.0	70.0	80.0		
╛	36"		70.0	80.0	70.0	80.0	70.0	80.0		
╛	42"	120"	70.0	80.0	70.0	80.0				-
┛	48"		70.0	74.4	70.0	80.0				
╛	54"		59.7	59.7	70.0	80.0	_	-		
	60"		51.0	51.0	70.0	80.0				
4	30"		70.0	80.0	70.0	80.0	70.0	80.0		
1	36"		70.0	80.0	70.0	80.0	_			
4	42"	132"	70.0	80.0	70.0	80.0	-			
4	48"		70.0	71.1	70.0	80.0	-			
1	54"		56.5	56.5	70.0	80.0	-	-		
4	30"		70.0	80.0	70.0	80.0	70.0	80.0		
1	36"	144"	70.0	80.0	70.0	80.0	_			
1	42"		70.0	80.0	70.0	80.0	_			
1	48"		68.6	68.6	70.0	80.0	_	_		

# NOTES:

- 1. WINDOW SIZE DIMENSIONS SHOWN ARE MAXIMUM SIZES. SMALLER SIZES SHALL APPLY TO LOADS EQUAL TO THE NEAREST LARGER SIZE SHOWN IN TABLE.
- SIZE SHOWN IN TABLE.

  2. IF NO LOAD IS SHOWN FOR A SPECIFIED WINDOW SIZE, THAT SIZE MAY NOT BE USED WITH THE RESPECTIVE GLASS OPTION.



6 TITLE ALUMINUM CLAD WOOD SASH GLAZED FIXED IMPACT WINDOWS	MANUFACTURER	KML WINDOWS, INC.	23 BUCHANAN COURT	LONDON, ONTARIO, CANADA N5Z	(519) 681–7012
DRAWING TITLE ALUMINUM CLAD WOOD SAS	CONSULTANTS	W. W. SCHAEFER ENGINEERING	& CONSULTING, P.A.	8895 N. MILITARY TRAIL; SUITE C-204 PAIN PEACH CAPPENS FI 33410	PHONE: 561-775-4902 FAX: 561-775-4903
CERTIFICATION 11N 18 7003		11	/		ARREN W. SCHAEFER, P.E. P.F. NO. 44135

DRAWING NO. 1226A

7 of 8

DRAWN BY: K.P.S.

DATE: 05/13/03

NOTE: HEIGHT & WIDTH CAN BE INTERCHANGED

	MATERIAL LIST						
PART NO.	REF. NO.	DESCRIPTION	NOTES				
		PARTS &	EXTRUSIONS				
1	PF1010	LINEAL JAMB	SEE NOTE 1 THIS SHEET.				
2	PF1231	RADIAL JAMB	LAMINATED VENEER				
3	PF1454	LINEAL SASH	SEE NOTE 1 THIS SHEET.				
4	PF1454	RADIAL SASH	LAMINATED VENEER				
5	PF1455	LINEAL SASH STOP	SEE NOTE 1 THIS SHEET.				
6	PF1455	RADIAL SASH STOP	LAMINATED VENEER				
7	PF1008	LINEAL GLAZING STOP	SEE NOTE 1				
8	PF1008	RADIAL GLAZING STOP	LAMINATED VENEER				
9	PF1001	RADIAL FRAME CLADDING	ALUMINUM 6063-T5				
9A	РМС73	MULLION CAP	ALUMINUM 6063-T5				
9B	PF1002	LINEAL FRAME CLADDING	ALUMINUM 6063-T5				
10	PF1018	RADIAL SASH CLADDING	ALUMINUM 6063-T5				
11	PF1017	RADIAL GLASS STOP	ALUMINUM 6063-T5				
12	PF1074	LINEAL SASH CLADDING	ALUMINUM 6063-T5				
13	PF1214 or PF1326	VINYL NAILING FINS	OPTIONAL				
14	SK1031	GALVANIZED 16 GA. STEEL INSTALLATION CLIP	GALVANIZED STEEL, INC. (Fy = 33 KSI MIN.) 4" FROM CORNERS & 12" O.C.				
15	PF1026	0.415" X 0.489" RAINSKIRT	SCHLEGEL: EXTRUDED FLEXIBLE COPOLYMER				
		FASTI	ENERS				
16	_	#8 x 2" SMS SCREW (JAMB TO SA	SH) 4" FROM CORNERS & MAX. 10" O.C.				
17	-	#8 x 5/8" PAN HEAD SMS SCREW	3 PER INSTALLATION CLIP INTO JAMB				
18		#10 SMS SCREW WITH MINIMUM 1 3/8" EMBED INTO THE BUCK (JAMB TO BUCK)	4" FROM CORNERS & MAX. 12" O.C.				
19	-	#8 x 1 1/4" SMS SCREW	2 PER CLIP INTO BUCK (1 EA. SIDE OF BUCK)				
20	_	S/STL #8 x 1 1/4" SMS SCREW OR 1 5/8" DRYWALL SCREWS	4" FROM ENDS & MAX. 10 1/2" O.C. WITH FIN				
21	_	#6 x 3/4" SMS SCREW	3" FROM CORNERS & 8" O.C.				
21A		#6 x 3/4" SMS SCREW	2" FROM CORNERS & 12" O.C.				
22		#6 x 1 5/8" SMS SCREW	3" FROM CORNERS & 8" O.C.				
23		#8 X 1 1/4" SMS	3" FROM CORNERS & 12" O.C.				
24	_	3/8" LONG STAPLE	3" FROM CORNERS & MAX. 8" O.C				
25A	-	#8 x 2" SMS SCREW	4 @ EA. RECTANGULAR JAMB CORNER & 2 AT EA. RECTANGULAR SASH CORNER				
25B	_	#8 x 1 1/2" SMS SCREW	3 @ EACH RADIUS JAMB CORNER & 2 AT EA. RADIAL SASH CORNER				
26	-	#6 x 3/4" SMS SCREW	2 @ EA. JAMB CLAD CORNER 1 @ EA. SASH CLAD CORNER				

	MATERIAL LIST						
PART NO.	REF. NO.	DESCRIPTION	NOTES				
		SEAL	ANTS				
28	-	DOW 995 SILICONE	FOR 1/2" GLAZING BITE				
29		DOW 1199 STRUCTURAL SILICONE ADHESIVE	CONTINUOUS CLADDING TO JAMB & SASH				
	OTHER						
30	_	NORTON NORGLAZE .0625" X .437" GLAZING TAPE	POLYOLEFIN FOAM W/ ACRYLIC ADHESIVE  TRIM OFF AT EDGES (TYP. AT CLAD CORNERS)				
31		TREMCO 440 BUTYL TAPE GASKET	TRIM OFF AT EDGES (TYP. AT CLAD CORNERS)				



ALL WOOD USED WITH TESTED UNITS IS MINIMUM GRADE 2 PONDEROSA PINE. ALTERNATE WOOD SPECIES ACCEPTABLE WITH THIS PRODUCT ARE THE FOLLOWING MINIMUM GRADE 2

WOODS: 1. MAHOGANY

- 2. OAK
- 3. CHERRY
- 4. CYPRUS
- 5. DOUGLAS FIR
- 6. MAPLE
- 7. TEAK

GLAZED FIXED IMPACT WINDOWS KML WINDOWS, INC. 23 LONDON, C SASH CLAD WOOD 19 DRAWING NO. 1226A SHEET NO. 8 OF 8

DATE: 05/13/03

